

SLISTECH

PRO 4C - 20 Pin Plug

Shielded - Yellow (0.5mm ²)	11	Home Position Input	Trigger Input	1	Shielded - Green (0.5mm ²)
Yellow (0.5mm ²)	12	Air Temp	Water Temp	2	Purple (0.5mm ²)
Green / Black (0.5mm ²)	13	GPI-1 Input Signal	TPS Signal	3	Grey / Red (0.5mm ²)
Red / White (0.5mm ²)	14	5 Volt Sensor Positive	Tacho Output	4	Blue / Grey (0.5mm ²)
White / Black (0.5mm ²)	15	GPO 1 Output	Ignition Output 3	5	Yellow / Red (0.5mm ²)
Yellow / Green (0.5mm ²)	16	Ignition Output 2	Ignition Output 1	6	Yellow / Black (0.5mm ²)
Green / Red (0.5mm ²)	17	GPI-2 Input Signal	To Fuel Relay	7	Grey (0.5mm ²)
Blue (1.5mm ²)	18	Idle Control Negative	To Ignition Switched +12V	8	Red (0.5mm ²)
Brown / Green (1.5mm ²)	19	Injector Negative 2	Main Earth	9	Black (1.5mm ²)
Brown / Black (1.5mm ²)	20	Injector Negative 1	Main Earth	10	Black (1.5mm ²)

SLISTECH

PRO 4C - 10 P_{in} P_{lug}

White / Blue (0.5mm ²)	6	GPO 2 Output	Ignition Output 4	1	Yellow / Blue (0.5mm ²)
White / Green (0.5mm ²)	7	GPO 3 Output	Earth	2	Black (1.5mm ²)
Red / Yellow (2.0mm ²)	8	Battery +13.8 Volt		3	No Connection
Green / Blue (0.5mm ²)	9	GPI-3 Input Signal	Earth	4	Black (1.5mm ²)
Brown / Yellow (1.5mm ²)	10	Injector Negative 3	Injector Negative 4	5	Brown / Blue (1.5mm ²)